



**DETAIL**

**NOTES:**

1. MINIMUM WIDTH OF STEPS IS 3 FEET FOR RESIDENTIAL PROPERTY, 4 FEET FOR COMMERCIAL PROPERTY.
2. NUMBER OF STEPS WILL BE DETERMINED BY OVERALL RISER HEIGHT.
3. RISERS AND TREADS ARE TO BE OF UNIFORM SIZE AND SHAPE.
4. RISER IS TO BE BETWEEN 4 INCHES AND 7 INCHES. TREAD IS TO BE 11 INCHES MINIMUM.
5. TOLERANCE BETWEEN LARGEST AND SMALLEST RISER/TREAD IS NOT TO EXCEED  $\frac{3}{8}$  INCH IN ANY SET OF STEPS.
6. SAW CUT EXISTING SIDEWALK FULL DEPTH.
7. ROUND OR CHAMFER ALL EDGES  $\frac{1}{2}$  INCH.
8. BROOM FINISH ALL SURFACES TRANSVERSELY TO FLOW OF TRAFFIC.

<b>CITY OF ROCHESTER</b>		
<b>CONCRETE STEP AT BUILDING</b>		
ISSUED	5-31-12	<b>NON-STANDARD DWG.NO.S608-35</b>
REVISED		