



PAVEMENT SECTION	X" BASE COURSE	A (Ø PIPE)	B (BOTTOM TRENCH)
LIGHT-DUTY	0"	1'-10½"	2'-6½"
MEDIUM-DUTY	3"	2'-1½"	2'-9½"
MODIFIED	6"	2'-4½"	3'-0½"
HEAVY-DUTY	8"	2'-6½"	3'-2½"

NOTES :

1. APPLY TACK COAT TO UNEXPOSED FACE OF CURB AND BETWEEN ALL LIFTS OF HMA COURSES.
2. HMA COURSES TO BE EITHER 60, 70 OR 80 SERIES COMPACTION AS REQUIRED IN CONTRACT DOCUMENTS.
3. SEAL ALL TOP COURSE JOINTS WITH ASPHALT PAVEMENT JOINT ADHESIVE IN ACCORDANCE WITH NYS DOT SECTION 418 ASPHALT PAVEMENT JOINT ADHESIVE.
4. SEE DETAIL R609-1 FOR STONE CURB.

CITY OF ROCHESTER		
<h2 style="margin: 0;">ASPHALT PAVEMENT SECTION WITH CURB</h2>		
ISSUED	9-2-91	STANDARD
REVISED	8-10-21	DWG.NO.R400-1