



SIGN BOARD:

- SIZE 36" x 36"
- ORANGE BACKGROUND WITH INNER BLACK LINE
- CLEAR MARGIN $\frac{5}{8}$ " ALL AROUND
- INNER BLACK LINE $\frac{7}{8}$ " WIDE

LETTERS:

- BLACK, 4" TYPE C WITH 4" LINE SPACING

NOTES:

1. SIGN TO BE PLACED MINIMUM OF 20 FEET IN ADVANCE OF ROAD PLATE, WITH OUTER EDGE OF SIGN MINIMUM OF 2 FEET OFF EDGE OF PAVEMENT.
2. BOTTOM OF SIGN TO BE MINIMUM OF 5 FEET ABOVE GROUND.
3. SIGN TO BE LOCATED SUCH AS TO ACHIEVE MAXIMUM VISIBILITY, WITHOUT INTERFERING WITH SIGHT DISTANCE FOR PEDESTRIANS, BICYCLISTS AND MOTORISTS.
4. FLASHING BEACON TO BE AFFIXED TO TOP OF SIGN POST, TO BE FULLY OPERATIONAL 24 HOURS PER DAY, WITH FLASHER FACING ONCOMING TRAFFIC.

CITY OF ROCHESTER		
RAISE PLOW ROAD PLATE AHEAD WARNING SIGN		
ISSUED	4-25-96	NON-STANDARD DWG.NO.S999-I
REVISED	1-6-22	